

# VITELLO

## TECHNICAL CHARACTERISTICS / TEKNİK ÖZELLİKLER

<b>FABRIC COMPOSITION / KUMAŞ İÇERİĞİ</b>	<b>%100 POLYESTER</b>
---	-----------------------

TEST TYPES / TEST TİPİ	ASPECT / KRİTER	NORM	UNIT / BİRİM	STANDART TEST
<b>WEIGHT / AĞIRLIK</b>		430 ± %10	g / m <sup>2</sup>	ISO 2286-2
<b>TEAR STRENGTH / YIRTILMA DİRENCİ</b>	<b>ACROSS / EN</b>	> 20	N	ISO 13937-2
	<b>ALONG / BOY</b>	> 20	N	ISO 13937-2
<b>TENSILE STRENGTH / KOPMA DİRENCİ</b>	<b>ACROSS / EN</b>	> 350	N	ISO 1421
	<b>ALONG / BOY</b>	> 350	N	ISO 1421
<b>ELONGATION AT BREAK / KOPMA ANINDAKİ UZAMA</b>	<b>ACROSS / EN</b>	> 100	%	ISO 1421
	<b>ALONG / BOY</b>	> 60	%	ISO 1421
<b>LAMINATION ADHESION / LAMİNASYON YAPIŞMASI</b>		> 10	N	ISO 2411
<b>MARTINDALE - ABRASION / AŞINMA DAYANIMI</b>		>20.000	RUB (12kPa)	ISO 12947
<b>COLOR FASTNESS TO RUBBING / SÜRTÜNME RENK HASLIĞI</b>	<b>DRY / KURU</b>	≥ 4,0	GS	ISO 105-X12
	<b>WET / ISLAK</b>	≥ 3,5	GS	ISO 105-X12

